



PEMCO 230 10W-30 PM0230

Hydro-synthetic universal motor oil for all types of gasoline engines. Designed to meet VW and DAIMLER requirements.

Product properties:

- The hydrosynthetic base ensures efficient operation of the engine in all operating modes: during cold start, in urban mode and in highway mode;
- Due to its good washing and dispersing properties and high thermal oxidative stability, it effectively fights against all types of deposits (carbon deposits, varnishes) and keeps engine parts clean throughout the entire interval between replacements;
- Contains an effective set of antioxidants due to which it effectively resists aging;
- Saves fuel due to the low viscosity base;
- The hydro-synthetic base combined with a modern additive package preserves engine power parameters throughout the entire interval between replacements;
- Applicable for diesel engines.

Designed for gasoline and diesel engines in a wide fleet of cars (cars, light utility vehicles, vans and light trucks) of European and other manufacturers.

Recommended for use in engines of Daimler, VW vehicles that impose additional requirements for engine oils (according to the above specifications), when API SN or lower performance is required, as well as ACEA A3/B4.

The oil is not suitable for use in heavy trucks and similar vehicles!

SPECIFICATION

- SAE 10W-30

RECOMMENDATION

- API SN
- ACEA A3/B4
- VOLKSWAGEN 505 00
- VOLKSWAGEN 501 01
- MB 229.1
- ISUZU
- KIA